

# **INSTRUCTION SHEET**

Part Number

**Application:** 1953–2015 C1–C7 Corvette

114-025

## **Part Includes**

- 1 Caliper Paint
- 1 Caliper Cleaner
- 1 Stir Stick
- 1 Paint Brush
- 1 Roll of Masking Tape





**Tools Needed** 

### READ DIRECTIONS AND PRECAUTIONARY WORDING CAREFULLY.

Paint requires 2 hours to dry before installing wheels. Allow 24 hours for paint to fully cure prior to vehicle use. Use of rubber gloves is recommended.

DO NOT use brake caliper paint on braking surfaces such as discs, drums, brake pads or shoes. If paint should come in contact with these surfaces, clean immediately or replace parts. Read precautions on container before use. Apply product according to instructions and in a well-ventilated dust free environment. Apply when air temperature is between 55–85° F. Brake dust may contain asbestos. Wear safety glasses and a face mask when cleaning brake components. Block tires to keep vehicle from rolling. Always use jack stands when working underneath a vehicle.

### STEP 1.

Remove all 4 wheels from vehicle. Calipers and/or drums do not need to be removed. For best caliper results, unbolt caliper and remove brake pads. Do not remove brake line.

### STEP 2.

Clean surfaces to be painted with enclosed Dupli-Color Caliper Cleaner. Read directions and precautionary wording before use. Spray surface with Caliper Cleaner.

# STEP 3.

Scrub Caliper Cleaner on caliper with a clean toothbrush or equivalent. Wipe dry with a clean towel. Be sure to remove all brake dust and/or contaminants.

#### STEP 4.

Masking of the surrounding area is recommended. Tape off the brake bleeder screw, brake lines and caliper piston boots.

# STEP 5.

Remove lid from paint can. Stir contents thoroughly for 1 minute with enclosed stir stick.

# STEP 6.

Apply paint to the caliper or drum with enclosed brush in thin, even strokes. Allow paint to set-up for 15–20 minutes between coats. Apply additional coats as needed to even out brush strokes and obtain full coverage. Apply second coat within 1 hour or wait 5 days.





MAMotorworks



Midamotorworks



MidAmericaMotorworks

2900 N. Third Street, P.O. Box 1368, Effingham, IL 62401 800.500.1500 • Worldwide: 217.540.4200 • FAX: 217.540.4800 www.mamotorworks.com • mail@mamotorworks.com


©Mid America Motorworks, Inc. All rights reserved.



# **Brake Caliper Paint** (cont.)

114-025

1.



2.



3.



4.



5.



6.

