



Application: 1953-2015 Corvette

Part Includes

1 - Battery Cleaner Aerosol Can

Battery Cleaner



Tools Needed



STEP 1.

Provide adequate ventilation.

STEP 2.

Shake can with ball agitator for one minute. For best results, aerosol can should be at room temperature before spraying.

STEP 3.

Holding can 8 to 10 inches from the surface to be cleaned, press the nozzle and discharge the product onto the corroded area. The product discharges as a foam.

STEP 4.

Let stand for approximately 5 minutes.

STEP 5.

Flush with water using a gentle flow to avoid splashing the dissolved corrosion.

STEP 6.

Wipe battery clean with rag, shop cloth or paper towel.

STEP 7.

For best results, seal terminals with a battery protector/sealer. Store in a cool, dry location in unopened containers at a temperature between 8° and 28° C (46° and 82° F) unless otherwise labeled. Optimal storage is at the lower half of this temperature range.

PRODUCT BENEFITS

- Removes power-robbing corrosion
- Fast acting
- Penetrates - no disassembly required

TYPICAL APPLICATIONS

- Batteries
- Cables
- Terminal connections



MAMotorworks



Midamotorworks



MidAmericaMotorworks

2900 N. Third Street, P.O. Box 1368, Effingham, IL 62401
800.500.1500 • Worldwide: 217.540.4200 • FAX: 217.540.4800
www.mamotorworks.com • mail@mamotorworks.com

©Mid America Motorworks, Inc. All rights reserved.