



**Application:** Beetle, Super, Ghia, Bus, Type 3, Thing, Vanagon, 1946-2015

**Part Includes**

1 - Battery Cleaner

## Battery Cleaner



**Tools Needed**



**STEP 1.**

Provide adequate ventilation.

**STEP 2.**

Shake can with ball agitator for one minute. For best results, aerosol can should be at room temperature before spraying.

**STEP 3.**

Holding can 8 to 10 inches from the surface to be cleaned, press the nozzle and discharge the product onto the corroded area. The product discharges as a foam.

**STEP 4.**

Let stand for approximately 5 minutes.

**STEP 5.**

Flush with water using a gentle flow to avoid splashing the dissolved corrosion.

**STEP 6.**

Wipe battery clean with rag, shop cloth or paper towel.

**STEP 7.**

For best results, seal terminals with a battery protector/sealer. Store in a cool, dry location in unopened containers at a temperature between 8° and 28° C (46° and 82° F) unless otherwise labeled. Optimal storage is at the lower half of this temperature range.

**PRODUCT BENEFITS**

- Removes power-robbing corrosion
- Fast acting
- Penetrates - no disassembly required

**TYPICAL APPLICATIONS**

- Batteries
- Cables
- Terminal connections



MAMotorworks



Midamotorworks



MidAmericaMotorworks

**2900 N. Third Street, P.O. Box 1368, Effingham, IL 62401**  
**800.500.1500 • Worldwide: 217.540.4200 • FAX: 217.540.4800**  
**www.mamotorworks.com • mail@mamotorworks.com**

©Mid America Motorworks, Inc. All rights reserved.