

Revision Date 11-May-2020

SAFETY DATA SHEET

Version 4

1. IDENTIFICATION

Product identifier Product Name

126VR DISC BRAKE QUIET 0.25 FL.OZ POUCH

Other means of identification Product Code

Recommended use of the chemical and restrictions on useRecommended UseAdhesiveUses advised againstNo information available

80729

Details of the supplier of the safety data sheet Manufacturer Address ITW Permatex 6875 Parkland Blvd. Solon, Ohio 44139 USA Telephone: 1-87-Permatex (866) 732-9502 24-hour emergency phone number Chem-Tel: 800-255-3924 International Emergency: 00+1+ 813-248-0585 Contract Number: MIS0003453

E-mail address: mail@permatex.com

May Also Be Distributed by: ITW Permatex Canada 101-2360 Bristol Circle Oakville, ON Canada L6H 6M5 Telephone: (800) 924-6994

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Serious eye damage/eye irritation	Category 2A
Carcinogenicity	Category 1A
Reproductive toxicity	Category 1B
Specific target organ toxicity (single exposure)	Category 3

Label elements

Emergency Overview

<u>Signal word</u> Danger

Causes serious eye irritation May cause cancer May damage fertility or the unborn child May cause respiratory irritation May cause drowsiness or dizziness



Appearance Blue

Physical state Liquid

Odor Alcohol

Precautionary Statements - Prevention

Obtain special instructions before use Do not handle until all safety precautions have been read and understood Use personal protective equipment as required Wash face, hands and any exposed skin thoroughly after handling Wear eye/face protection Avoid breathing dust/fume/gas/mist/vapors/spray Use only outdoors or in a well-ventilated area

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Precautionary Statements - Storage

Store locked up Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

Toxic to aquatic life with long lasting effects. Toxic to aquatic life.

Unknown acute toxicity

0% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
2-PROPANOL	67-63-0	40 - 70
BUTYL BENZYL PHTHALATE	85-68-7	5 - 10
TALC	14807-96-6	3 - 7

4. FIRST AID MEASURES

Description of first aid measures

General advice

Get medical advice/attention if you feel unwell.

Eye contact IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Skin contact	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.	
Inhalation	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If symptoms persist, call a physician.	
Ingestion	IF SWALLOWED:. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician.	
Self-protection of the first aider	Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.	
Most important symptoms and effe	cts, both acute and delayed	
Symptoms	See section 2 for more information.	
Indication of any immediate medical attention and special treatment needed		
Note to physicians	Treat symptomatically.	
5. FIRE-FIGHTING MEASURES		

Suitable extinguishing media

Carbon dioxide (CO2), Use dry chemical, Foam

Unsuitable extinguishing media

Do not use a solid water stream as it may scatter and spread fire

Specific hazards arising from the chemical

Highly flammable. Vapors may form explosive mixtures with air.

Explosion data

Sensitivity to Mechanical ImpactNone.Sensitivity to Static DischargeNone.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions	Ensure adequate ventilation, especially in confined areas. Avoid contact with eyes and skin. Use personal protective equipment as required. Remove all sources of ignition. Take precautionary measures against static discharges.		
Environmental precautions			
Environmental precautions	See section 12 for additional ecological information.		
Methods and material for containment and cleaning up			
Methods for containment	Prevent further leakage or spillage if safe to do so.		
Methods for cleaning up	Eliminate all ignition sources if safe to do so. Ensure adequate ventilation. Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal.		
Prevention of secondary hazards	Clean contaminated objects and areas thoroughly observing environmental regulations.		

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling	Handle in accordance with good industrial hygiene and safety practice. Avoid breathing vapors or mists. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Wash contaminated clothing before reuse. Remove all sources of ignition. Take precautionary measures against static discharges.		
Conditions for safe storage, including any incompatibilities			

 Storage Conditions
 Store in a well-ventilated place. Keep cool. Store locked up.

Incompatible materials Strong oxidizing agents, Amines

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH	
2-PROPANOL	STEL: 400 ppm	TWA: 400 ppm	IDLH: 2000 ppm	
67-63-0	TWA: 200 ppm	TWA: 980 mg/m ³	TWA: 400 ppm	
		(vacated) TWA: 400 ppm	TWA: 980 mg/m ³	
		(vacated) TWA: 980 mg/m ³	STEL: 500 ppm	
		(vacated) STEL: 500 ppm	STEL: 1225 mg/m ³	
		(vacated) STEL: 1225 mg/m ³	-	
TALC	TWA: 2 mg/m ³ particulate matter	(vacated) TWA: 2 mg/m ³ respirable	IDLH: 1000 mg/m ³	
14807-96-6	containing no asbestos and <1%	dust <1% Crystalline silica,	TWA: 2 mg/m ³ containing no	
	crystalline silica, respirable	containing no Asbestos	Asbestos and <1% Quartz	
	particulate matter	TWA: 20 mppcf if 1% Quartz or	respirable dust	
		more;use Quartz limit		

NIOSH IDLH Immediately Dangerous to Life or Health

Other Information

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Appropriate engineering controls

Engineering Controls	Showers
	Eyewash stations
	Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/face protection	Wear safety glasses with side shields (or goggles).
Skin and body protection	Wear protective natural rubber, nitrile rubber, Neoprene™ or PVC gloves.
Respiratory protection	Use NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as appropriate.
General Hygiene Considerations	Handle in accordance with good industrial hygiene and safety practice. Regular cleaning of equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical propertiesPhysical stateLiquidAppearanceBlueOdorAlcohol

Odor threshold	No information available	
Property	Values	Remarks • Method
рН	No information available	
Melting point / freezing point	No information available	
Boiling point / boiling range	No information available	
Flash point	12 °C / 54 °F	Tag Closed Cup
Evaporation rate	No information available	
Flammability (solid, gas)	No information available	
Flammability Limit in Air		
Upper flammability limit:	12.7%	
Lower flammability limit:	2.0%	
Vapor pressure	33 mm Hg @ 68°F	
Vapor density	>1	Air = 1
Relative density	0.91	
Water solubility	Insoluble in water	
Solubility(ies)	No information available	
Partition coefficient	No information available	
Autoignition temperature	No information available	
Decomposition temperature	No information available	
Kinematic viscosity	No information available	
Dynamic viscosity	No information available	
Explosive properties	No information available	
Oxidizing properties	No information available	
Other Information		
Softening point	No information available	
Molecular weight	No information available	
VOC Content (%)	60.2962	
Density	No information available	
Bulk density	No information available	
SADT (self-accelerating	No information available	
decomposition temperature)		

10. STABILITY AND REACTIVITY

Reactivity

No information available

Chemical stability

Stable under normal conditions

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

Strong oxidizing agents, Amines

Hazardous Decomposition Products

Carbon oxides

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation

May cause irritation of respiratory tract. May cause drowsiness or dizziness.

Eye contact	Contact with eyes may cause	se irritation. May cause redn	ess and tearing of the eyes
-------------	-----------------------------	-------------------------------	-----------------------------

Skin contact May cause skin irritation and/or dermatitis.

Ingestion Ingestion may cause irritation to mucous membranes.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
2-PROPANOL	5050 mg/kg	12800 mg/kg	= 72600 mg/m ³ (Rat) 4 h
67-63-0			
BUTYL BENZYL PHTHALATE	= 2330 mg/kg (Rat)	= 6700 mg/kg (Rat)	> 6.7 mg/L (Rat)4 h
85-68-7			

Information on toxicological effects

Symptoms

No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization	No information available.			
Germ cell mutagenicity	No information available.			
Carcinogenicity	The table below	indicates whether each	agency has listed any ing	redient as a carcinogen.
Chemical Name	ACGIH	IARC	NTP	OSHA
BUTYL BENZYL	-	Group 3	-	-
PHTHALATE				
85-68-7				
TALC	-	Group 3	-	Х
14807-96-6		-		
IARC (International Age	ency for Research on Cancer)			
Group 1 - Carcinogenic t	o Humans			
Not classifiable as a hum	0			
	afety and Health Administration	n of the US Department of	Labor)	
X - Present				
Target Organ Effects	Central Vascula	r System (CVS), Eyes, R	espiratory system, Skin.	
The following values are ATEmix (oral)	calculated based on chapt 6163 mg/kg	er 3.1 of the GHS docu	ment .	

ATEmix (oral)6163 mg/kgATEmix (dermal)16433 mg/kgATEmix (inhalation-dust/mist)32 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

0 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Mobility

No information available.

Chemical Name	Partition coefficient
2-PROPANOL 67-63-0	0.05
BUTYL BENZYL PHTHALATE 85-68-7	3.57 - 4.91

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes	This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).
Contaminated packaging	Do not reuse container.
US EPA Waste Number	D001

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
2-PROPANOL	Toxic
67-63-0	Ignitable

14. TRANSPORT INFORMATION

DOT UN/ID No Proper shipping name: Hazard Class Packing Group Emergency Response Guide Number	1133 Adhesives, Limited Quantity (LQ) 3 II 128
IATA UN/ID No Proper shipping name: Hazard Class ERG Code	ID 8000 Consumer commodity 9 9L
IMDG UN/ID No Proper shipping name: Hazard Class Packing Group EmS-No	1133 Adhesives, Limited Quantity (LQ) 3 II F-E, S-D

International Inventorie	s	
TSCA	Complies	
DSL/NDSL	Complies	
EINECS/ELINCS	Not determined	
ENCS	Not determined	
IECSC	Complies	
KECL	Complies	
PICCS	Complies	
AICS	Not determined	

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory **DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

- **ENCS** Japan Existing and New Chemical Substances
- **IECSC** China Inventory of Existing Chemical Substances
- **KECL** Korean Existing and Evaluated Chemical Substances
- **PICCS** Philippines Inventory of Chemicals and Chemical Substances
- AICS Australian Inventory of Chemical Substances

US Federal Regulations

<u>SARA 313</u>

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
2-PROPANOL - 67-63-0	1.0
SARA 311/312 Hazard Categories	
Acute health hazard	Yes
Chronic Health Hazard	Yes
Fire hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
BUTYL BENZYL PHTHALATE	-	Х	Х	-
85-68-7				

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
BUTYL BENZYL PHTHALATE	100 lb	-	RQ 100 lb final RQ
85-68-7			RQ 45.4 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65
BUTYL BENZYL PHTHALATE	Developmental
85-68-7	
LLO Otata Binkt ta Kuasu Banulatiana	^

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
2-PROPANOL	Х	X	Х
67-63-0			
BUTYL BENZYL PHTHALATE	Х	X	Х
85-68-7			
TALC	X	X	X
14807-96-6			

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

WHMIS Hazard Class

B2 - Flammable liquid, D2A - Very toxic materials, D2B - Toxic materials

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA	Health hazards 2	Flammability 3	Instability 0	- Personal protection B
HMIS	Health hazards 2	Flammability 3	Physical hazards 0	

NFPA (National Fire Protection Association) HMIS (Hazardous Material Information System)

Revision Date

11-May-2020

Disclaimer

Illinois Tool Works Inc. believes the information contained in this data sheet is accurate as of the date compiled. However, Illinois Tool Works Inc. makes no warranty, express or implied, as to the accuracy, reliability or completeness of the information. User is responsible for evaluating whether such information or this product is fit for a particular purpose and suitable for a particular use or application. The information in this data sheet may not be valid if this product is used in combination with other products or in processes for which it was not designed. Illinois Tool Works Inc. disclaims any liability for consequential or incidental damages of any kind, including lost profits, arising from the sale or use of this product. Ensure you have the most current version of this data sheet by contacting us or reviewing our web site.

End of Safety Data Sheet