



Foaming Tire Cleaner

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 07/10/2018

Version: 1.1

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : Foaming Tire Cleaner

1.2. Recommended use and restrictions on use

Recommended use : Auto care product

1.3. Supplier

Griot's Garage Inc.
3333 South 38th Street, Tacoma, WA 98409
2185 Airwest Blvd., Plainfield, IN 46168
Telephone: 800-345-5789
Fax: 888-252-2252
Email: info@griotsgarage.com
Website: www.griotsgarage.com

1.4. Emergency telephone number

Emergency number : 800-345-5789

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

Liquefied gas; Skin Irrit. 2; Eye Dam. 1

2.2. GHS Label elements, including precautionary statements

GHS-US labeling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) : **DANGER**
Hazard statements (GHS-US) : Contains gas under pressure; may explode if heated
Causes serious eye damage. Causes skin irritation.
Precautionary statements (GHS-US) : Protect from sunlight and do not expose to temperatures exceeding 50 °C/122 °F.
Wear protective gloves/eye protection.
Wash hands and exposed skin thoroughly after handling.

2.3. Other hazards which do not result in classification

Contains: Citrus oils – May produce an allergic reaction in persons already sensitized.

2.4. Unknown acute toxicity (GHS US)

Not applicable

Foaming Tire Cleaner

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS-US classification
Propane	(CAS No) 74-98-6	2 - 5	Flam. Gas 1; H220 Liquefied gas; H280
Butane	(CAS No) 106-97-8	2 - 5	Flam. Gas 1; H220 Liquefied gas; H280
Silicic acid, disodium salt (1:2)	(CAS No) 6834-92-0	1 - 2	Skin Corr. 1B; H314 Eye Dam. 1; H318 STOT SE 3; H335 Met. Corr. 1; H290
Tetrasodium salt of ethylenediamine tetraacetic acid, dihydrate	(CAS No) 64-02-8	< 1	Acute Tox. 4; H302, H332 Eye Dam. 1; H318
1-Octanesulfonic acid, sodium salt (1:1)	(CAS No) 5324-84-5	< 1	Acute Tox. 4; H302, H332 Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT SE 3; H335 Aquatic Acute 2; H401 Aquatic Chronic 3; H412
Alcohols, C12-14-secondary, ethoxylated	(CAS No) 84133-50-6	< 1	Skin Irrit. 2; H315 Eye Dam. 1; H318 Aquatic Acute 2; H401
Lemon Twist	(CAS No) Mixture	< 1	Flam. Liq. 3; H226 Skin Irrit. 2; H315 Skin Sens. 1B; H317 Asp. Tox. 1; H304
Isopropanol	(CAS No) 67-63-0	< 0.1	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336
Sodium hydroxide	(CAS No) 1310-73-2	< 0.1	Met. Corr. 1; H290 Skin Corr. 1A; H314 Eye Dam. 1; H318
Trisodium Nitrioltriacetate	(CAS No) 5064-31-3	< 0.1	Acute Tox. 4; H302 Eye Irrit. 2; H319 Carc. 2; H351
Water	(CAS No) 7732-18-5	> 85	Not classified as dangerous for transport.
Sodium sulfate	(CAS No) 7757-82-6	< 0.1	Not classified as dangerous for transport.

Additional Information - Substances in the product which may present a health or environmental hazard, or which have been assigned occupational exposure limits, are detailed below.: **None**

* The exact percentage withheld as a trade secret in accordance with 29 CFR 1910.1200.

SECTION 4: First-aid measures

Foaming Tire Cleaner

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation	: Not normally required. If symptoms occur obtain medical attention.
First-aid measures after skin contact	: Wash affected skin with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Do not give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell. Rinse mouth.

4.2. Most important symptoms and effects (acute and delayed)

Causes serious eye damage. Contains: Citrus oils – May produce an allergic reaction in persons already sensitized.

4.3. Immediate medical attention and special treatment, if necessary

No additional information available

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Extinguish with carbon dioxide, dry chemical, foam or water spray.
Unsuitable extinguishing media	: Do not use water jet.

5.2. Specific hazards arising from the chemical

Contains gas under pressure; may explode if heated. Leaking containers may release flammable gases that can accumulate in poorly ventilated areas.

5.3. Special protective equipment and precautions for fire-fighters

Advice for fire-fighters	A self contained breathing apparatus and suitable protective clothing should be worn in fire conditions. Keep containers cool by spraying with water if exposed to fire.
---------------------------------	--

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes. Avoid breathing vapors.

6.2. Environmental precautions

Prevent release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	: Cover spills with inert absorbent material. Transfer to a container for disposal or recovery.
-------------------------	---

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes. Avoid breathing vapors.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Keep in a cool, well ventilated place. Store at temperatures not exceeding 50 °C / 122 °F.
Incompatible materials	: This product should be stored away from sources of strong heat or oxidizing chemicals.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

SUBSTANCE.	CAS No.	(8hr TWA)		(STEL)		Note:
		PEL (OSHA)	TLV (ACGIH)	PEL (OSHA)	TLV (ACGIH)	
Propane	74-98-6	1000 ppm	Aspyx.#	-----	-----	#
n-Butane	106-97-8	-----	250 ppm	-----	-----	-----

#Assure minimum oxygen content of work atmosphere.

Recommended monitoring method

NIOSH 1500 (hydrocarbons, B.P. 36 - 126 °C)

8.2. Appropriate engineering controls

Foaming Tire Cleaner

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Appropriate engineering controls

Provide adequate ventilation to ensure that the occupational exposure limit is not exceeded.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Hand Protection:

Wear suitable gloves if prolonged skin contact is likely. Check with protective equipment manufacturer's data. Use gloves only once.

Eye protection:

Wear protective eyewear (goggles, face shield, or safety glasses).

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Check with protective equipment manufacturer's data.

Thermal Hazards:

Not normally needed. Use gloves with insulation for thermal protection, when needed.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Aerosol
Color.	Not available
Odor	Not available
Odor Threshold (ppm)	Not available
pH (Value)	Not available
Melting Point (°C) / Freezing Point (°C)	Not available
Boiling point/boiling range (°C):	Not available
Flash Point (°C)	-104 (Propane)
Evaporation Rate	Not available
Flammability (solid, gas)	Contains: Extremely flammable gas.
Explosive Limit Ranges	2.1% - 9.5% v/v (Propane)
Vapor pressure (Pascal)	ca. 95×10^4 (Propane)
Vapor Density (Air=1)	ca. 1.56 @ 0°C (Propane)
Density (g/ml)	Not available
Solubility (Water)	Not available
Solubility (Other)	Not available
Partition Coefficient (n-Octanol/water)	Not available
Auto Ignition Point (°C)	450 (Propane)
Decomposition Temperature (°C)	Not available
Kinematic Viscosity	Not available
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions.

10.2. Chemical stability

Stable under normal conditions of storage and use.

10.3. Possibility of hazardous reactions

None anticipated.

10.4. Conditions to avoid

Avoid contact with heat and ignition sources.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

Foaming Tire Cleaner

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Carbon monoxide, Carbon dioxide, Acrid smoke.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Exposure routes: Inhalation, Skin Contact, Eye Contact

Information on toxicological effects

Propane (CAS# 74-98-6):

Acute toxicity	Inhalation: LC50 = 1237 mg/L (2-hr, mouse, gas)
Irritation/Corrosivity	No evidence of irritant effects from normal handling and use.
Sensitisation	It is not a skin sensitizer.
Repeated dose toxicity	NOAEC: \geq 19678 mg/m ³ (28-day, rat, Systemic effects) LOAEC: 21641 mg/m ³ (28-day, rat, effects: Body weight)
Carcinogenicity	No data. It is unlikely to present a carcinogenic hazard to man.
Mutagenicity	There is no evidence of mutagenic potential.
Reproductive toxicity	None anticipated

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity

Short term	Not to be expected.
Long Term	Not to be expected.

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods	Disposal should be in accordance with local, state or national legislation. Consult an accredited waste disposal contractor or the local authority for advice.
--------------------------------	--

SECTION 14: Transport information

	<u>U.S. DOT</u>	<u>Sea transport (IMDG)</u>	<u>Air transport (ICAO/IATA)</u>
UN number	1950	1950	1950
Proper Shipping Name	Aerosols, non-flammable	Aerosols, non-flammable	Aerosols, non-flammable
Transport hazard class(es)	2.2	2.2	2.2
Packing group	Not applicable	Not applicable	Not applicable
Environmental hazards	None assigned	None assigned	None assigned
Special precautions for user	None assigned	None assigned	None assigned

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code: Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

Safety, health, and environmental regulations/legislation specific for the substance or mixture:

TSCA (Toxic Substance Control Act) - Inventory Status: All components listed or polymer exempt.

Designated Hazardous Substances and Reportable Quantities (40 CFR 302.4): None

SARA 311/312 - Hazard Categories: See SECTION 2 - HAZARDS IDENTIFICATION

SARA 313 - Toxic Chemicals (40 CFR 372): None

SARA 302 - Extremely Hazardous Substances(40 CFR 355): None

Foaming Tire Cleaner

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 16: Other information

Other information : None.

Hazard Statement(s) and Risk Phrases Listed in: SECTION 2:/ SECTION 3:

Hazard Statement(s)

- H220: Extremely flammable gas.
- H225: Highly flammable liquid and vapor.
- H226: Flammable liquid and vapour.
- H280: Contains gas under pressure; may explode if heated.
- H290: May be corrosive to metals.
- H302: Harmful if swallowed.
- H304: May be fatal if swallowed and enters airways.
- H314: Causes severe skin burns and eye damage.
- H315: Causes skin irritation.
- H317: May cause an allergic skin reaction.
- H318: Causes serious eye damage.
- H319: Causes serious eye irritation.
- H332: Harmful if inhaled.
- H335: May cause respiratory irritation.
- H336: May cause drowsiness or dizziness.
- H351: Suspected of causing cancer.
- H401: Toxic to aquatic life.
- H412: Harmful to aquatic life with long lasting effects.

The data presented here relates only to the specific material designated herein and does not relate to use in combination with any other materials or in any process. The information set forth above is based on technical data believed to be reliable. It is intended for use by persons having technical skill and at their own discretion and risk. Since conditions of use are outside our control, no warranties, expressed or implied are made, and no liability is assumed in connection with any use of this information. Judgments as to the suitability of this information for the user's purposes are necessarily the user's responsibility. Although reasonable care has been taken in the preparation of this information, no responsibility is assumed as to the accuracy or suitability of this information for its application to the user's intended purpose or for consequences of its use.