



Application: All Years

Part Includes

Black Anodized Trim Paint



Tools Needed



Search: **Paint**

www.mamotorworks.com

Formulated with patented "adhere" polymers for application on chrome and alloy trim. Color matched to highest quality anodized alloy trim.

DANGER! EXTREMELY FLAMMABLE! CONTENTS UNDER PRESSURE. VAPOR HARMFUL

BLACK-Anodize Chrome and Trim Paint creates a tough, scratch-resistant satin black finish on chrome, polished aluminum, and alloys of most types. Restores showroom new appearance to worn anodized trim or created new visual concepts.

DIRECTIONS FOR SAFE AND PROPER APPLICATION

STEP 1.

Clean surface to remove wax, grease, dirt, and grime. Surface must be dry before applying.

STEP 2.

Mask windows and areas not to be sprayed. Also cover surrounding areas to protect them from overspray.

STEP 3.

Spray at room temperature. Do not apply at temperatures below 70 degrees F.

STEP 4.

Test spray a small area before proceeding with complete application.

STEP 5.

Shake can for one minute after mixing ball rattles, then continue to shake can occasionally while spraying.

STEP 6.

Hold can 12" to 16" away from surface being sprayed. Do not cover with a continuous spray, but release the spray button after each stroke and overlap. Light coats are better than heavy coats.

STEP 7.

If clogging develops, remove spray button with a twisting motion and clean. Do not stick pins or other objects into can. Gently replace spray button with a twisting motion with top of can and spray button opening pointing away from you.

STEP 8.

Clean spray button immediately after use by turning can upside down and pressing spray button until no more paint comes out.



Mamotorworks



@CorvettePassion



MidAmericaMotorworks



CorvettePassion

2900 North Third Street, Effingham, IL 62401

800.500.1500 • Worldwide: 217.540.4200 • FAX: 217.540.4800

www.mamotorworks.com • generalmail@mamotorworks.com

©Mid America Motorworks, Inc. All rights reserved.



Description (cont.)

DO NOT wax, buff or polish with abrasives.

Important notice to purchaser: The following warranty is in lieu of all other express or implied warranties, namely that this product is manufactured with first class materials and under the most rigid scientific quality controls. The liabilities of the manufacturer and/or distributors shall not exceed the purchase price of this can. Manufacturers and/or vendor assume no responsibility, express or implied, for results of misuse or misapplication, or for any injury that might be sustained through ingestion, inhalation, or absorption through any body surface.

WARNINGS: Keep FROM HEAT, SPARKS AND OPEN FLAME. Vapor Harmful. Contents under pressure. DO NOT PUNCTURE, INCINERATE (BURN) OR STORE ABOVE 120 degrees F. Exposure to heat or prolonged exposure to sun may cause bursting. Contains (solvent). Use only with adequate ventilation. Avoid contact with eyes, prolonged or repeated contact with skin or continuous breathing of vapors or spray mist. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS CAN BE HARMFUL OR FATAL. In case of eye contact, immediately flush thoroughly with water and get medical attention. CONTAINS TOLUOL AND XYLOL.