



**Application:** All Years

# Black Reconditioning Paint



## Tools Needed



Search: **Paint**

[www.mamotorworks.com](http://www.mamotorworks.com)

**DANGER! EXTREMELY FLAMMABLE! CONTENTS UNDER PRESSURE. VAPOR HARMFUL. MAY CAUSE FLASH FIRE.**

*Performance Choice Black Reconditioning Paint is a fast drying high quality lacquer for underhood & chassis use. Excellent for recoating damaged components. It features a fanspray valve which produces professional results. A wide, even spray for smoother, faster coverage, especially on large areas.*

### DIRECTIONS FOR USE

#### STEP 1.

Clean surface thoroughly. Remove grease, oil, loose paint, rust, etc. Sand previously painted areas lightly, then clean with a high grade solvent and allow to dry before spraying. Bare metal should be primed.

#### STEP 2.

Mask areas not to be sprayed. Also protect surrounding areas from overspray.

#### STEP 3.

Painting should be done in a well ventilated area. Test a small area before proceeding with complete application. Do not apply at temperatures below 70 degrees F (21 degrees C).

#### STEP 4.

SHAKE CAN WELL at least one minute after ball rattles. Repeat occasionally during use.

#### STEP 5.

Hold can 8 to 10 inches from surface. Press spray button firmly. Do not apply with continuous spray. Move back and forth releasing the button after each stroke. Overlap each stroke.

#### STEP 6.

To prevent clogging after spraying, turn can upside down and press sprayhead for about 3 seconds. This will clean button slot. Do not stick objects into can opening.

#### STEP 7.

Discard empty can in trash pick-up. Do not incinerate or compact.

### WARNING CONTAINS TOLUOL

**DANGER! EXTREMELY FLAMMABLE.** Do not spray near sparks, heat or open flames. Vapors will accumulate readily and may ignite explosively. Keep area ventilated during use and until all vapors are gone. **DO NOT SMOKE** – Extinguish all flames, pilot lights and heaters – Turn off stoves, electric tools, and appliances, and other sources of ignition. **CONTENTS UNDER PRESSURE.** Avoid prolonged exposure to sunlight or heat from radiators, stoves, hot water and other heat sources that may cause bursting. Do not puncture, incinerate, burn or store above 120 degrees. Do not discard empty can in home garbage compactor. **VAPOR HARMFUL.** Use with adequate ventilation. Avoid continuous breathing of vapors or spray mist. Open windows and doors or use other means to ensure



Mamotorworks



@CorvettePassion



MidAmericaMotorworks



CorvettePassion

**2900 North Third Street, Effingham, IL 62401**

**800.500.1500 • Worldwide: 217.540.4200 • FAX: 217.540.4800**

**[www.mamotorworks.com](http://www.mamotorworks.com) • [generalmail@mamotorworks.com](mailto:generalmail@mamotorworks.com)**

©Mid America Motorworks, Inc. All rights reserved.



## **Description (cont.)**

fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air or wear respiratory protection (NIOSH/MSHA TC 23C or equivalent) or leave the area. Can be absorbed through skin.

**HARMFUL OR FATAL IF SWALLOWED.** If swallowed do not induce vomiting. Call physician immediately.

**WARNING:** Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain damage and nervous system damage to arms and legs. Can be absorbed through skin causing blood, lung, liver and kidney effects. This product also contains chemical(s) known by the state to cause cancer, birth defects or other reproductive harm. Risk to your health depends on level and duration of exposure. **INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS MAY BE HARMFUL OR FATAL.**

**KEEP AWAY FROM CHILDREN.**