




Application: 2014-2018

Parking Sensor Installation



Tools Needed



Part Includes

- 1-Chassis Harness
- 1-Power Harness with RCA Connectors
- 1-Camera mounted on bracket
- 2-License Plate Bolts
- 1-Male to Male RCA Adapter
- 1-Alternate Camera Mount

SAFETY PRECAUTIONS:

- Work in well ventilated area that is clear of obstructions.
- Secure vehicle with tire chucks in both front and rear of tires.
- Turn vehicle accessories OFF and ensure ignition key is in OFF position.
- Wear safety goggles and snug fitting clothes.
- Use tools only for their intended purpose and which are in good repair.
- Only perform this task if confidence, skill, and ability permit.

STEP 1.

Determine which of the two supplied camera mounting methods that you prefer. (License Plate Bracket or Alternate Camera Mount Bracket.)

Place camera in desired position to confirm fitment (**NOTE:** Some states prohibit items blocking the license plate; check local authorities to confirm legal status for your application).

-If using **LICENSE PLATE BRACKET**, remove license plate. Reattach license plate securing bracket behind.


-If using **ALTERNATE CAMERA MOUNTING BRACKET**, remove camera from license plate bracket using supplied Allen wrench. Attach camera to the Alternate Camera Mount bracket and apply supplied self-adhesive foam to mount.

Use the Template included in the installation instruction overview to position the Alternate Camera Mount on vehicle.

Clean vehicle surface to which mount is to be attached and affix with self-adhesive foam. We recommend permanent attachment using screws.

STEP 2.

Measure, mark, and drill a 1/4" hole for camera harness. **NOTE:** if your vehicle has a liftgate panel/trunk trim cover, it must be removed.



STEP 3.

Determine location of vehicle power and ground. Using a vehicle specific service guide and or specific wiring diagram and a multi-meter or computer safe test light, locate which side of the vehicle contains Ignition and Ground wires (Chart A)




Chart A

Wire Color	Polarity	Function	Description	Location
Red	12v +	Ignition controlled power	This lead will display 12 volt + when the key is in the RUN position	Commonly found on main Ignition harness.
Black	(-)	Ground	Chassis ground	A ground bolt is commonly found in the front kick panel area with other wires attached.

CAUTION: Once the wires have been identified, turn Ignition key **OFF** and **DO NOT TURN** key back **ON** until the installation is complete.



Mamotorworks



@CorvettePassion



MidAmericaMotorworks

2900 North Third Street, Effingham, IL 62401

800.500.1500 • Worldwide: 217.540.4200 • FAX: 217.540.4800

www.mamotorworks.com • generalmail@mamotorworks.com


©Mid America Motorworks, Inc. All rights reserved.



Description (cont.)

STEP 4:

Splice the red and black Power Harness leads into the corresponding vehicle wires. (We recommend soldering or T-taps as optional connection method.) Also recommended is an eyelet for the ground connection.



STEP 5.

Insert the connector end of the camera harness through the hole you drilled. (We recommend that you protect Camera Harness from sharp metal edges by applying small amount of silicone caulk or a rubber grommet to the area that comes into contact with the metal.)


STEP 6.

Route the camera harness. Continue routing harness to the side of the vehicle that supplies power and then forward.



STEP 7.

Connect Camera Harness to supplied Chassis Harness. The optimal location for this junction may occur at the top of the liftgate or the inner edge of the trunk depending on vehicle in which installation is in. (**NOTE:** most vehicles may already have existing wires passing through this area; use this route if at all possible.)




STEP 8.

Route Chassis Harness. It may be necessary to remove sill plates, pillar covers, seat bottoms, side panels, etc. In some cases even the seatbelt bolts at the bottom of the pillars must be removed. (**CAUTION:** Any bolts removed for safety devices must be tightened to manufacturer's torque specifications). Use a plastic trim removal tool to avoid damage to trim pieces.




STEP 9.

Secure Camera Harness to existing vehicle wiring. This will minimize the chance of binding or otherwise damaging the harness. We recommend wire ties or electrical tape.



STEP 10.

Connect Chassis Harness to supplied Power Harness.



STEP 11.


Install aftermarket display/ Navigation display as per instructions (if required.)



Description (cont.)

STEP 12.

Connect the male RCA from the Power Harness to the "Camera IN" on the aftermarket display/ Navigation display.



STEP 13.

Test the system. Inspect that all connections are proper and secure. Clear all loose items removed from the area around the vehicle and turn the ignition key ON to test the system.

STEP 14.

Adjust the camera angle (if necessary). Loosen camera screw using supplied Allen wrench to aim the camera. Tighten screw at desired adjustment.

STEP 15.

Reassemble vehicle. Follow your disassembly steps in reverse order, taking care not to bind the harness wiring when reinstalling.

NOTE: This camera has grid lines or non grid lines and mirror image or non mirror image options.

GRID LINE OPTIONS:

The default setting is to display grid lines. To remove the grid line display, connect the two green wires near the end of the camera harness.

DISPLAY OPTIONS:

Default setting is mirror image display for rearward facing camera (rear view) installation. To change to non mirror image for forward facing camera (front view) connect the two white wires near the end of the camera harness.